

DF-18 model dehumidifiers are portable dehumidifiers for small spaces. According to the water tank, the moisture taken can be kept in the device or the drain line can be connected to a fixed line. With the humidity level indicator, the instantaneous humidity of the space can be monitored and the desired humidity level, fan speed and timing settings can be made via the control panel.



| Model | DH-18 |
|---------------------------|--|
| Code | 45400018 |
| Dehumidification Capacity | 18 liters/day (30°C and 80% relative humidity) |
| Air Circulation | 250 m³/h (2-stage) |
| Operating Temperature | 5°C to 32°C |
| Power Consumption | 220 W (220V/50Hz) |
| Water Tank Capacity | 1.6 liters |
| Weight | 10.5 kg |
| Measures | 290 x 275 x 470 mm (W x L x H) |



| , D U 00 | |
|---------------------------|--|
| Model | DH-20 |
| Code | 45400020 |
| Dehumidification Capacity | 20 liters/day (30°C and 80% relative humidity) |
| Air Circulation | 180-240 m³/h(2 stages) |
| Operating Temperature | 5°C to 38°C |
| Power Consumption | 280W (220V/50Hz) |
| Water Tank Capacity | 6 liters |
| Weight | 15 kgs |
| Measures | 370 x 255 x 615 mm (W x L x H) |

DH-50 Room Dehumidifiers



DH-50 model dehumidifiers are produced portable for medium-sized (80-160 m3) areas. It can be used for daily and commercial purposes. The drain line of the device can be connected to a fixed drain line. Thanks to the humidity level indicator, the instantaneous humidity of the area can be monitored and the desired humidity level, fan speed and timing can be adjusted via the control panel.



| Model | DH-50 |
|---------------------------|--|
| Code | 45400050 |
| Dehumidification Capacity | 50 liters/day (30°C and 80% relative humidity) |
| Air Circulation | 780 m³/h(2 stages) |
| Operating Temperature | 5°C to 38°C |
| Power Consumption | 850 W (220V/50Hz) |
| Water Tank Capacity | 6 liters |
| Weight | 26 kgs |
| Measures | 360 x 440 x 630 mm (W x L x H) |