

Flexible Hose



T-GAS



Black reinforced hose with crush-resistant nylon coil for a maximum temperature of 200°C. It is suitable for attaching to reels and for duct or floor-mounted systems. It is highly recommended because of its flexibility, lightness, and durability.

T-SPECIAL4



Aluminum glass fabric flexible hose with externally sewn high tensile steel coil. Color: Silver grey with black rubbing stripe. Operating temperature: 400°C. Suitable for attaching rewinding reels and stationary systems. not crush resistant

Hose Diameter (mm)	Hose Length	T-Gas Model	T-Gas Code	Special 4 Model	Special 4 Code
B 75	2,5	75,2,5	51700702		
B 75	5	75/5	51700705		
B 75	7,5	75/7,5	51700707		
B 75	10	75/10	51700710		
B 75	13	75/13	51700713		
B 75	15	75/15	51700715		
B 75	20	75/20	51700720		
B 75	40	75/40	51700740		
B 100	2,5	100/2,5	51701002	100/2,5	51721002
B 100	5	100/5	51701005	100/5	51721005
B 100	7,5	100/7,5	51701007	100/7,5	51721007
B 100	10	100/10	51701010	100/10	51721010
B 100	13	100/13	51701013		
B 100	15	100/15	51701015		
B 100	20	100/20	51701020		
B 100	40	100/40	51701040		
B 125	2,5			125/2,5	51721202
B 125	5	125/5	51701205	125/5	51721205
B 125	7,5	125/7,5	51701207	125/7,5	51721207
B 125	10	125/10	51701210	125/10	51721210
B 125	13	125/13	51701213		
B 125	15	125/15	51701215		
B 125	17	125/17	51701217		
B 125	20	125/20	51701220		
B 125	40	125/40	51701240		
B 150	2,5			150/2,5	51721502
B 150	5	150/5	51701505	150/5	51721505
B 150	7,5	150/7,5	51701507	150/7,5	51721507
B 150	10	150/10	51701510	150/10	51721510
B 150	13	150/13	51701513		
B 150	15	150/15	51701515		
B 150	20	150/20	51701520		
B 180	2,5			180/2,5	51721802
B 180	5			180/5	51721805
B 180	7,5			180/7,5	51721807
B 180	10	180/10	51701810	180/10	51721810
B 180	20	180/20	51701820		
B 200	2,5			200/2,5	51722002
B 200	5			200/5	51722005
B 200	7,5			200/7,5	51722007
B 200	10	200/10	51702010	200/10	51722010
B 200	20	200/20	51702020		