



- High output air stream for entrances up to 2,5 meter height.
- Electrical heating, water heated or ambient models are available.
- Modular design for each door length. Flexible connection and easy mounting.
- Adjustable air flow direction.
- Independent control over fan speed and heat output.
- Automatic cut out against overheating. (High limit thermostat)
- Aluminum crossflow fans.
- NiCr tube resistance to improve efficiency.
- Automatic cooling system.
- Corrosion proof steel housing with electrostatic powder paint coated.
- Thermally protected motor.
- High temperature resistant polyamide side covers.
- Various control systems and color options due to the customer demands
- 2 year warranty

Model	Dimensions (L x H x W)	Heating Capacity (KW)	Electrical Supply	Supply rating	Sound level Db	Maximum Air Speed (m/s)	Maximum Flow Rate (m³/h)	Mounting Height (m)	Weight (Kg)	Code
H25100A	1050X235X310	n/a	240V-1ph	0.65	57/53	9	1400	2.5	17	30251001
H25100W	1050X235X310	9	240V-1ph	0.65	56/52	8	1250	2.5	19	30251002
H25100E	1050X235X310	4.5/9	400V-3ph	13.5	57/53	9	1400	2.5	21	30251003
H25150A	1570X235X310	n/a	240V-1ph	0.65	58/54	9	2300	2.5	23	30251501
H25150W	1570X235X310	13.5	240V-1ph	0.65	57/53	8	2100	2.5	26	30251502
H25150E	1570X235X310	675/13.5	400V-3ph	20	58/54	9	2300	2.5	27	30251503
H25200A	2050X235X310	n/a	240V-1ph	0,9	58/54	9	2800	2.5	34	30252001
H25200W	2050X235X310	18	240V-1ph	0,9	57/53	8	2500	2.5	38	30252002
H25200E	2050X235X310	9\18	400V-3ph	27	58/54	9	2800	2.5	42	30252003
H25250A	2620x235x310	n/a	240V-1ph	0.13	60/56	9	3700	2.5	40	30252501
H25250W	2620x235x310	22.5	240V-1ph	22.5	59/55	8	3350	2.5	45	30252502
H25250E	2620x235x310	11.5/22.5	400V-3ph	33.5	60/56	9	3700	2.5	48	30252503

LPHW at 80/60°C and 18°C ambient temperature

For each phase

According to the measurement made at a distance
of 3 m from the air flow

Accessory

Kind	Explanation	Code
CB-W/A	Control panel for ambient/hot water heated units	30300003
CB-E Series	Control panel for electrically heated unit	30300004
CBA-W/A	Built-in control panel for ambient hot water heated units	30300005
CBA- E	Built-in control panel for electrically heated unit	30300006
LK-W/A	Modular connection kit for ambient/hot water heated unit	30300008
LK-E	Modular connection kit for electrically heated unit	30300009
E-CB-E	Remote control for electric heated unit with door key option	30301000
CB-BMS	Intelligent control system with electric heating or ambient air curtain	30300013
CB-BMS-W	Water heated air curtain intelligent control system	30300014

CB BMS

- Control box with led display
- Indoor and outdoor temperature sensor
- Control by signal from the door switch
- Energy efficiency with comfort mode and economy mode
- Automatic fan and heating level change according to the difference between indoor and outdoor temperature
- BMS connection via Modbus
- Stage control with 3 fans and heaters

CB-E



CBA-W/A



E- CB -E



CB BMS

