



## Power Driven Rewinding Reels with Fan

### AEV/AERV Model

Motor driven hose reel with push button for the rollup And the roll-down of the flexible hose for Extraction.suitable for wall or ceiling installation. Complete with electric safety stop and remote start And stop of the centralized fan (centralized as Optional). Differs from "AE/AER" model in the coupling with an "LAM" series electric exhauster; this model provides excellent extraction even with a flexible hose up to 13 metres long. It is particularly suitable for use in workshop where autonomous workstations are needed. Exhausters switchon/off is automatically regulated by the lowering/raising controls of the hose.

### AEV/AERV-MAXI Model

Motor driven hose reel with fan and with push button For the roll-up and the roll-down of the flexible Hose for extraction.suitable for wall or ceiling installation. Complete with electric safety stop and Remote start and stop of the centralized fan (Operation by pushbutton panel or remote control).Differs from "AE/AER-MAXI model in the coupling with an "LAM" series electric exhauster. This model provides excellent extraction even with a flexible hose up to 17metres long. It is particularly suitable for use in workshop where autonomous workstations are needed. Exhausters switch-on/off is automatically regulated by the Lowering/raising controls of the hose.

Model	Hose Diameter (mm)	Hose Type	Hose Length (m)	Engine Power	Weight (kg)	Code
AEV/AERV -75/7	Ø 75	T-GAS	7	0,5	56	51300707
AEV/AERV-75/10	Ø 75	T-GAS	10	0,5	58	51300710
AEV/AERV-75/13	Ø 75	T-GAS	13	0,5	61	51300713
AEV/AERV-100/7	Ø 100	T-GAS	7	0,5	60	51301007
AEV/AERV-100/10	Ø 100	T-GAS	10	0,5	63	51301010
AEV/AERV-100/13	Ø 100	T-GAS	13	0,5	66	51301013
AEV/AERV-125/7	Ø 125	T-GAS	7	1	65	51301207
AEV/AERV-125/10	Ø 125	T-GAS	10	1	68	51301210
AEV/AERV-125/13	Ø 125	T-GAS	13	1	71	51301213
AEV/AERV-125/17	Ø 125	T-GAS	7	1,5	75	51301217
AEV/AERV-125/20	Ø 125	T-GAS	20	1,5	78	51301220
AEV/AERV-150/10	Ø 150	T-GAS	10	1	73	51301510
AEV/AERV-150/15	Ø 150	T-GAS	15	1	78	51301515
AEV/AERV-150/17	Ø 150	T-GAS	17	1,5	80	51301517
AEV/AERV MAXI-125/15	Ø 125	T-GAS	15	1,5	75	51311215
AEV/AERV MAXI-125/17	Ø 125	T-GAS	17	1,5	77	51311217
AEV/AERV MAXI-150/13	Ø 150	T-GAS	13	1,5	79	51311513
AEV/AERV MAXI-180/10	Ø 180	T-GAS	10	1,5	75	51311810
AEV/AERV MAXI-200/10	Ø 200	T-GAS	10	1,5	78	51312010

Optionally, the T-SPECIAL 4 can be used for a temperature of 400°C or the T-SPECIAL 10 for a temperature of 1000°C.