



With the AIRWIN UB dry warm air soon disappears, because it effectively humidifies the air and refreshes it.

The AIRWIN UB may be applied directly for specific humidification of

- Salad bars
- · Cheese counters
- Fish counters
- · Flower counters
- · Vegetable counters
- · Sausage and meat counters,
- · Room humidification by air ducts
- At any place where optimal and specific humidification is required.



## **Properties**

- The AIRWIN UB is made of non-corrosive high-quality steel. It is ready for operation. Only water and electrical energy services must be connected on the spot. The safety equipment includes thermal protection, overflow and dry-running protection.
- Ultrasonic humidifiers are controllable without starting delay and without overrun.
- UB series on/off control by hygrostat.
- UB-FB series with potentiometers in the remote control for separate output control, each output between 0 and 100%.
- Aqua Drain flushes the water supply lines, empties the water reservoir of the UB in cycles, empties the water reservoir after short periods of "nonhumidification" and power failures. The compact ventilator only works on humidification requests.



Model	Capacity (kg/h)	Voltage (V/Hz)	Electricity Consumption (VA)	Fuse Rating (A)	Measures H/L/W (mm)	Code
UB-1/FB	0,5	230/50	105	7.2	179,5/253/274	40104601-FB
UB-2/FB	1,0	230/50	135	7.4	179,5/253/274	40104602-FB
UB3-3/FB	1,5	230/50	165	7.6	179,5/253/274	40104603-FB
UB4-4/FB	2,0	230/50	195	7.8	179,5/253/274	40104604-FB
UB-12/FB	6,0	48/50	450	9.4	268/368/992	40104504-FB
UB-18/FB	9,0	48/50	675	14.1	268/368/992	40104505-FB
UB-24/FB	12,0	48/50	900	18.75	268/368/992	40104506-FB



Model	Capacity (kg/h)	Voltage (V/Hz)	Electricity Consumption (VA)	Fuse Rating (A)	Measures H/LW (mm)	Code
UB1	0,5	230/50	105	7.2	179,5/253/274	40104601
UB2	1,0	230/50	135	7.4	179,5/253/274	40104602
UB3	1,5	230/50	165	7.6	179,5/253/274	40104603
UB4	2,0	230/50	195	7.8	179,5/253/274	40104604
UB12	6,0	48/50	450	9.4	268/368/992	40104504
UB18	9,0	48/50	675	14.1	268/368/992	40104505
UB24	12,0	48/50	900	18.75	268/368/992	40104506