

XL and XLS types of home heating and wide range of commercial uses. They have a field of application. The settings of the XL series smart radiators are controlled by the user in accordance with the weather conditions. The XLS series increases the level of comfort with its advanced automatic charging system and provides more economical use. In this advanced control system, the amount of heat stored in different weather conditions is balanced without the need for user intervention. The patented Twin Sensor, which is the heart of the system, provides automatic charging.

Properties

- Less than 150mm deep
- XL range features manually adjustable charge regulator to control the amount of heat stored during the charge period.
- XLS range features automatically adjustable charge regulator to control the amount of heat stored during the charge period.
- Running cost savings of up to 15% can be achieved using automatic controller (XLS) compared to manual static (XL) storage heaters.
- Room temperature boost control increases heat output when required and may be used automatically or manually.
- Easy to use controls, out of sight of young children.
- Frontal grille for efficient heat distribution.
- Secure wall fixings for safety.
- Feet may be fitted under carpet or on top of a suitable floor covering.
- Drip proof construction (IPX2 rated)

Model	Input Power (kW)	Charging Capacity (kWh)	Weight (kg)	Dimensions (mm)	Code
XL 6	0.85	5.95	41	700x332x170	60080106
XL 12	1.70	11.90	76	706x565x146	60080112
XL 18	2.55	17.85	109	706x793x146	60080118
XL 24	3.40	23.80	144	706x1021x146	60080124
XLS 6	0.85	5.95	41	700x332x170	60080206
XLS 12	1.70	11.90	76	706x565x146	60080212
XLS 18	2.55	17.85	109	706x793x146	60080218
XLS 24	3.40	23.80	144	706x1021x146	60080224

